

AMENDMENTS TO THE CLAIMS

- Claim 1. (Amended) An improved locked-center idler ~~of the type~~ having a pulley supported by a bearing, said bearing mounted upon a tension adjusting member, the improvement comprising:
said tension adjusting member being in communication with a dual function fastener.
- Claim 2. (Original) The improvement of claim 1 wherein said tension adjusting member comprises a cylindrical portion adapted to cooperate with an inner portion of a bearing and an eccentric bore axially there through.
- Claim 3. (Original) The improvement of claim 1 wherein said tension adjusting member comprises a reaction friction surface and a resistance friction surface.
- Claim 4. (Original) The improvement of claim 3 wherein said reaction friction surface cooperates with a reaction mating surface of said dual function fastener to produce a reaction torque upon said tension adjusting member greater than a resistance torque produced by a cooperation of said resistance friction surface with a mounting surface.
- Claim 5. (Original) The improvement of claim 1 wherein said tension adjusting member comprises an arm with a pulley mounting portion and a dual function fastener receiving bore.
- Claim 6. (Original) The improvement of claim 1 wherein said tension adjusting member comprises a cylindrical portion adapted to cooperate with an inner portion of a bearing, a pivot extending axially and offset from the center of said cylindrical portion, a curved slot opening through the length of said cylindrical portion and having a mean curvature with an arc that defines a radius about said pivot.

- Claim 7. (Original) A locked-center idler comprising:
a pulley supported by a bearing
said bearing mounted upon a tension adjusting member, and
said tension adjusting member in communication with a dual function fastener.
- Claim 8. (Original) The locked-center idler of claim 7 wherein said tension adjusting member comprises a cylindrical portion adapted to cooperate with an inner portion of a bearing and an eccentric bore axially there through.
- Claim 9. (Original) The locked-center idler of claim 7 wherein said tension adjusting member comprises a reaction friction surface and a resistance friction surface.
- Claim 10. (Original) The locked-center idler of claim 9 wherein said reaction friction surface cooperates with an reaction mating surface of said dual function fastener to produce a reaction torque upon said tension adjusting member greater than a resistance torque produced by a cooperation of said resistance surface with a mounting surface.
- Claim 11. (Original) The locked-center idler of claim 7 wherein said tension adjusting member comprises an arm with a pulley mounting portion and a dual function fastener receiving bore.
- Claim 12. (Original) The locked-center idler of claim 7 wherein said tension adjusting member comprises a cylindrical portion adapted to cooperate with an inner portion of a bearing, a pivot extending axially and offset from the center of said cylindrical portion, a curved slot opening through the length of said cylindrical portion and having a mean curvature with an arc that defines a radius about said pivot.
- Claim 13. (Original) A method of applying tension to a belt drive power transmission system comprising the steps of:
providing a pulley assembly,

mounting said pulley assembly upon a tension adjusting member,
attaching said tension adjusting member upon a mount that is substantially
immobile in relation to an engine cylinder block with a dual function
fastener,
training a power transmission belt about said pulley assembly,
applying tension to said power transmission belt by applying a tightening torque
to said dual function fastener, and
fixing the position of said tension adjusting member by applying said tightening
torque to said dual function fastener.